


DOLBY TER



✓ = standard ○ = optional

TECHNICAL FEATURES

COPY ROUTER UNIT

- Dual rotation speed spindle
- Tool coupling
- Quick locking of the spindle to facilitate tool changing
- Horizontal vices
- Jigs
- Retractable stops
- Vice jaw extension 805 mm (Rh and/or Lh)
- Side support surfaces 1800 mm (Rh and/or Lh)
- Ability to work with jigs or with mechanical stops
- Independent pneumatic tracer with double diameter selector
Ø 5 and Ø 8 mm
- Tool mist lubrication
- Minimum lubrication with pure oil
- Air filter group
- Supplementary retractable stop
- Supplementary retractable magnetic stop
- Change unit of measurement to inches

12.000 rpm

ER 16

✓

2

2

2

○

○

✓

1

✓

○

✓

○

○

○

○

DRILLING UNIT

- Motor power
- Number of chucks
- Double diameter bit Ø 6/12 mm shank Ø 10 mm
- Double diameter bit Ø 6/10 mm shank Ø 10 mm
- Distance between holes
- Hydraulic unit feed
- Bit rotation speed
- Boring unit height adjustment from 10 to 90 mm with manual
handwheel assisted by decimal display
- Transversal adjustment of the drilling unit with metric rod stroke
55 mm

1,1 kW

3

1

2

22 mm

✓

900 rpm

✓

✓

✓