JOB 1000 PLUS





✓ = standard



TECHNICAL FEATURES

| • | Frame max dimension 2500 mm x 2500 mm | / |
|---|--|---------------------------------------|
| • | Max support 200 Kg | \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ |
| • | Height of work table 900 mm | |
| • | Table pneumatic tilting 0° - 14° | |
| • | Working tools fitted on linear guides with high precision balls | |
| | recirculation slides | ✓ |
| • | Cutting frame direct dimension | |
| • | Frames pneumatic locking | |
| • | 3 spindle drilling unit | |
| • | Horizontal milling unit | |
| • | Hydro pneumatic punching unit for cutting the hardware (parallel | |
| | cut as MAICO MULTITREND, AGB, G-U, SIEGENIA TITAN) | 0 |
| • | Hydro pneumatic punching unit for cutting the hardware (MAICO | |
| | MULTIMATIC cut) | 0 |
| • | Hydro pneumatic punching unit for cutting the hardware (ROTO cut) | 0 |
| • | Hydro pneumatic punching unit for cutting the hardware (WIN- | |
| | KHAUS AUTOPILOT cut) | 0 |
| • | Hydro pneumatic punching unit for cutting the hardware (WIN- | |
| | KHAUS ACTIVPILOT cut) | 0 |
| • | BS-Multi-Max Duo adapter | 0 |
| • | Automatic screwdriver unit, LED pointer equipped with pneuma- | |
| | tic lifting and tilting screw loader system | 0 |
| • | Drilling unit; tang till to Ø 8 mm | 0 |
| • | Double bit drilling unit; tang Ø 5 mm | 0 |
| • | Drilling unit with pneumatic lifting; tang till to Ø 8 mm | 0 |
| • | Double bit drilling unit with pneumatic lifting; tang till to Ø 5 mm | 0 |
| • | Trays for accessories | 0 |
| • | Electronic calibre and electronic measuring roller table | 0 |
| • | Sashes pneumatic centring device kit for handle working | 0 |
| • | MAG 1000 - Vertical hardware storage | 0 |
| • | MAG 1000 O - Horizontal hardware element magazine | 0 |
| • | MAG 1000 O-PC - Horizontal hardware element magazine with | |
| | computer holder console | 0 |
| • | MAG 800 - Hardware storage trolley | 0 |

TILTING DEVICE - Tilting bench