



roller tables and measuring stoppers

Cutting process speed.



Quota GB ALU / Quota BG PVC

Electronic measuring roller table for aluminium glazing bead

Quota GB ALU

For aluminium glazing bead. Available bluetooth data reception.

Quota GB PVC

For pvc glazing bead. Available bluetooth data reception.



Quota VX / VX 400

Roller table with digital display and manual length stop positioning

Quota VX

Width of bar resting surface: 200 mm.

Quota VX 400

Width of bar resting surface: 400 mm.



Porter / Porter Quota 400

Loading roller table

Porter

Loading roller table with vertical rollers.

Porter Quota 400

Loading roller table.



Quota CX / CX 400

Roller table with electronic motorized length stop positioning control

Quota CX

Width of bar resting surface: 200 mm.

Quota CX 400

Width of bar resting surface: 400 mm.



Quota MR

Roller table with electronic motorized length stop positioning control

Quota MR

Width of bar resting surface: 200 mm.



Quota LX

Roller table with manual length stop positioning

Width of bar resting surface: 200 mm



= Electronic gauge

It measures the sash frame and transmits the data directly to the stop via Bluetooth, eliminating manual entry of measurements and reducing the risk of inaccuracies.

Maximum efficiency, minimum margin of error for an easier, faster and more precise.



Fom — One Group. Every Solution.

www.comall.it

The specifications and illustrations in this catalogue are only guideline, Comall therefore reserves the right to make any modifications it deems necessary for technical or commercial reasons at any time and without prior notification.



Comall

roller tables and
measuring stoppers
product range